

# 10W LED 4' T8 TUBE 95+ CRI

Efficacy 160 lm/W **External Driver-Easy Installation Use Existing Fixtures** Type-C



**SPECIFICATIONS** 

9.8 watts

160 lm/W

5000K

97

120 - 277 VAC

1,568 lumens

320 Degrees

Dry Location

914mm x 25mm

0-10V & 3-Step Dimming

or Integrated Bluetooth Mesh

External Driver, Custom UL Class 2

100,000 hours at 25°C or 77°F

-4°F -122°F (-20°C -50°C)

10 Years Non-Prorated UL, DLC, ETL, NSF

Average Wattage

Luminous Efficacy

Dimensions (MOL)

**Dimming Options** 

Ratings

Warranty

Driver

Life Span

Certification

Operating Temperature

CRI (Color Rendering Index)

Measured Output in Lumens Illumination Angle

Input Voltage



## FEATURES & BENEFITS

- \* Dimming Options: Integrated Bluetooth Mesh Or 0-10V and 3-Step Dimming
- \* Easy Installation Replace Ballast with Driver Using existing Tombstones and Wiring
- \* Dual Polarity Wiring
- \* Greater than 70% savings over fluorescent tube
- \* 10-year non-prorated warranty
- \* Glass Tube Design Higher Transparency
- \* Available in 1,2,3 and 4 lamps/driver combinations

## LED Green Light Model Number:

GL-T8-4F-C-10W-5000K-95CRI-X

### Specify Dimming Option (X):

- (B) Integrated Bluetooth Mesh
- (0) 0-10V
- (3) 3-Step Dimming

#### Installation Procedure:

Remove Ballast and Install LED Driver and replace Fluorescent tubes with Type-C Tube.





















