

1X4 RECESSED TROFFER 30W LED LAMP 95+ CRI

Efficacy 140 lm/W Dimming Options: 0-10 V 3-Step Dimming or Integrate Bluetooth Mesh Ready

4000K

Average Wattage

Luminous Efficacy

Dimensions (MOL)

Dimming Options

Ratings

Warranty

Driver

Life Span

Certification

Operating Temperature

CRI (Color Rendering Index)

Measured Output in Lumens Illumination Angle

Input Voltage

SPECIFICATIONS

30 watts

3985K

97

140.2 lm/W

120 - 277 VAC

4,206 lumens

180 Degrees

Dry Location

914mm x 25mm

0-10V & 3-Step Dimming

or Integrated Bluetooth Mesh

External Driver, Custom UL Class 2

100,000 hours at 25°C or 77°F

-4°F -122°F (-20°C -50°C)

10 Years Non-Prorated

UL, DLC, ETL, NSF



FEATURES & BENEFITS

- * 66% Energy saving over flourscent
- * High luminance and low power
- Super long life and simple installation
- * 10x longer life than fluorencent tube
- * Flicker-Free
- *95+CRI
- * No UV, No RF interference
- * No Mercury, RoHS Compliant
- * Dimming 0-10V plus 3-Step Dimming
- * Integrated Bluetooth Mesh

LED Green Light Model Number: GL-1x4-Troffer-30W-4000K-95CRI-X

- (B) Integrated Bluetooth Mesh
- (0) 0-10V
- (3) 3-Step Dimming

Specify Dimming Option (X):

Projection view:





















