edgreenlight*

2X2 RECESSED TROFFER 40W LED LAMP 95+ CRI

Efficacy 138 lm/W Dimming Options: 0-10 V 3-Step Dimming or Integrate Bluetooth Mesh Ready

4000K

led<mark>green</mark>light*

FEATURES & BENEFITS

* Exceeds Million Lamp Challenge Phase 2 specification

- * Dimming Options: Integrated Bluetooth Meshor 0-10 V and 3-Step Dimming
- * Super Simple Installation
- * Greater than 60% savings over fluorescent
- * 10-year non-prorated warranty

* Flicker Free


LED Green Light Model Number: GL-2x2-Troffer-40W-4000K-95CRI-X

Specify Dimming Option (X):

- (B) Integrated Bluetooth Mesh
- (0) 0-10V
- (3) 3-Step Dimming

Projection view:

CE



SPECIFICATIONS

Average Wattage	38.7 watts
Luminous Efficacy	138 lm/W
Input Voltage	95-305 VAC
ССТ	4020K
CRI (Color Rendering Index)	97
Measured Output	5,341 lumens
Illumination Angle	180 Degrees
Flicker %	Flicker-Free
Dimensions	23.76in x 23.76in x 1.77in
Life Span	100,000 hours at 25°C or 77°F
Operating Temperature	-4°F -122°F (-20°C -50°C)
Ratings	Damp or Dry Location
Warranty	10 Years Non-Prorated
Certification	ETL, UL
Driver	External Driver
Dimming Options	0-10V & 3-Step Dimming
	or Integrated Bluetooth Mesh
TM-30-18 Rf	90
TM-30-18 Rg	99

ledgreenlight*

WWW.LEDGREENLIGHTINT.COI

O GREENLIGHT INTERNATIONAL'S PRODUCTION PECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

NSF.