



2X4 RECESSED TROFFER 20W LED LAMP 95+ CRI

Efficacy 147 lm/W
Dimming Options: 0-10 V
3-Step Dimming or Integrate Bluetooth
Mesh Ready



4000K




FEATURES & BENEFITS

- * 66% Energy saving over fluorescent
- * High luminance and low power
- * Super long life and simple installation
- * 10x longer life than fluorescent tube
- * Flicker-Free
- * 95+ CRI
- * No UV, No RF interference
- * No Mercury, RoHS Compliant
- * Dimming 0-10V plus 3-Step Dimming
- * Integrated Bluetooth Mesh

LED Green Light Model Number:
GL-2x4-Troffer-20W-4000K-95CRI-X

Specify Dimming Option (X):
(B) Integrated Bluetooth Mesh
(0) 0-10V
(3) 3-Step Dimming

Projection view:



SPECIFICATIONS

Average Wattage	19.3 watts
Luminous Efficacy	147.7 lm/W
Input Voltage	95-305 VAC
CCT	4100K
CRI (Color Rendering Index)	96
Measured Output	2,851 lumens
Illumination Angle	180 Degrees
Flicker %	Flicker-Free
Dimensions	47.8" x 23.7" (1213 x 603 x 45mm)
Life Span	100,000 hours at 25°C or 77°F
Operating Temperature	-4°F -122°F (-20°C -50°C)
Ratings	Damp or Dry Location
Warranty	10 Years Non-Prorated
Certification	ETL, UL
Driver	External Driver
Dimming Options	0-10V & 3-Step Dimming or Integrated Bluetooth Mesh
TM-30-18 Rf	90
TM-30-18 Rg	99

LEDGREENLIGHTINT.COM

PRODUCTS ARE WARRANTED ONLY TO MEET LED GREENLIGHT INTERNATIONAL'S PRODUCTION DATA SHEET SPECIFICATIONS. PRODUCTS AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.
REV 02-2020



WWW.LEDGREENLIGHTINT.COM

