

2X4 RECESSED TROFFER 30W LED LAMP 95+ CRI

Efficacy 144 lm/W
Dimming Options: 0-10 V
3-Step Dimming or Integrate Bluetooth
Mesh Ready

4000K



FEATURES & BENEFITS

- * 66% Energy saving over flourscent
- * High luminance and low power
- * Super long life and simple installation
- * 10x longer life than fluorencent tube
- * Flicker-Free
- *95+CRI
- * No UV, No RF interference
- * No Mercury, RoHS Compliant
- * Dimming 0-10V plus 3-Step Dimming
- * Integrated Bluetooth Mesh

LED Green Light Model Number:

GL-2x4-Troffer-30W-4000K-95CRI-X

Specify Dimming Option (X):

- (B) Integrated Bluetooth Mesh
- (0) 0-10V
- (3) 3-Step Dimming

Projection view:



SPECIFICATIONS

| 2 | |
|-----------------------------|------------------------------------|
| Average Wattage | 30 watts |
| Luminous Efficacy | 144.7 lm/W |
| Input Voltage | 95-305 VAC |
| CCT | 3990K |
| CRI (Color Rendering Index) | 97 |
| Measured Output | 4,341 lumens |
| Illumination Angle | 180 Degrees |
| Flicker % | Flicker-Free |
| Dimensions | 47.8" x 23.7" (1213 x 603 x 45mm) |
| Life Span | 100,000 hours at 25°C or 77°F |
| Operating Temperature | -4°F -122°F (-20°C -50°C) |
| Ratings | Damp or Dry Location |
| Warranty | 10 Years Non-Prorated |
| Certification | ETL, UL |
| Driver | External Driver |
| Dimming Options | 0-10V & 3-Step Dimming |
| | or Integrated Bluetooth Mesh |
| TM-30-18 Rf | 90 |
| TM-30-18 Rg | 99 |
| X | |



















