

15.8 W LED 4' T8 TUBE 95+ CRI

Efficacy 158.6 lm/W **External Driver-Easy Installation Use Existing Fixtures** Type-C



SPECIFICATIONS

15.8 watts

158.6 lm/W 120 - 277 VAC

320 Degrees

Dry Location

914mm x 25mm

0-10V & 3-Step Dimming

or Integrated Bluetooth Mesh

External Driver, Custom UL Class 2

100,000 hours at 25°C or 77°F

-4°F -122°F (-20°C -50°C)

10 Years Non-Prorated

UL, DLC, ETL, NSF

5000K

96 2,506 lumens

Average Wattage

Luminous Efficacy

Dimensions (MOL)

Dimming Options

Ratings

Warranty

Driver

Life Span

Certification

Operating Temperature

CRI (Color Rendering Index)

Measured Output in Lumens Illumination Angle

Input Voltage



FEATURES & BENEFITS

- * Exceeds Million Lamp Challenge Phase 2 specificarion
- * Dimming Options: Integrated Bluetooth Mesh Or 0-10V and 3-Step Dimming
- * Easy Installation Replace Ballast with LED Driver Using existing Tombstones and Wiring
- * Dual Polarity Wiring
- * Greater than 60% savings over fluorescent tube
- * 10-year non-prorated warranty
- * Glass Tube Design Higher Transparency
- * Available in 1,2,3 and 4 lamps/driver combinations

LED Green Light Model Number:

GL-T8-4F-C-15W-5000K-95CRI-X

Specify Dimming Option (X):

- (B) Integrated Bluetooth Mesh
- (0) 0-10V
- (3) 3-Step Dimming

Installation Procedure:

Remove Ballast and Install LED Driver and replace Fluorescent tubes with Type-C Tube.





















