



# Tri-LED Lamp Pendant Mount Architectural Lamp

## BENEFITS

Stunning 4' - 45W Architectural design  
High luminance; low power consumption  
Super long life and simple installation  
10X longer life than fluorescent tube  
270 Degree Beam Angle  
High CRI >95  
No UV, No RF interference  
No Mercury, RoHS compliant  
Overhead Pendant Mount

LED Greenlight SKU: 4'-45W T8-Type  
Pendant Mount Lamp

GL-PMLEDL-45W-95-3500K  
GL-PMLEDL-45W-95-4100K  
GL-PMLEDL-45W-95-5000K

## SPECIFICATIONS

average wattage	45 Watts
luminous efficacy (tube)	115 lm/W
input voltage	100-277 VAC
color temps offered (ANSI)	3500K, 4100K or 5000K
CRI (color rendering index)	>95
measured output	>5200 lumens
beam angle	270 degrees
dimensions	1219mm X 101mm
life span	> 100,00 hours at 25°C or 77°F
operating temperature	-22°F-113°F
ratings	Indoor location
warranty	7 years non-prorated
certifications	UL, DLC CE
Driver	UL External Driver
power factor	>95% (277 VAC) :



[www.ledgreenlightint.com](http://www.ledgreenlightint.com)

