

2-T8 4' Strip Lamp LED Retrofit Kit

Retrofit Upgrade kit attaches directly
to existing T8 Strip Lamp.
Fresh New Appearance without
demolition of existing fixtures!

45W 5200 Lumens
95 CRI
DLC Listed



FEATURES & BENEFITS

Easy Installation – Attaches over existing fixture
using 4 self-tapping screws
No Ballast
>50% Energy Savings over fluorescent
High Luminance and Low Power consumption
Long Service Life 10X longer life than fluorescent
Wide-Light Distribution
High CRI 95
No UV, No RF interference
No Mercury, RoHS compliant
Instant ON and No Flicker

SPECIFICATIONS

average wattage	45 Watts
luminous efficacy	115 lm/W
input voltage	120-277 VAC
color temps offered (ANSI)	3500K, 4100K or 5000K
CRI (color rendering index)	95 CRI
measured output	5175 lumens
Illumination Angle	180 degrees
dimensions (MOL)	4 feet
life span	>100,000 hours
operating temperature	-4°F-122°F (-20°C-50°C)
ratings	dry location
warranty	7 years non-prorated
certification	DLC, ETL
Driver	External Driver - Integrated
power factor	>95% (277 VAC) :

INSTALLATION

- 1) Remove Fluorescent Lamps and Tombstones from Fixture
- 2) Open fixtures electrical access panel and attach "Quik-Connect" jack to input power line to ballast.
- 3) Connect fixtures power "Quik-Connect" to retrofit lamp.
- 4) Install retrofit over fixture-base via 4 self-tapping screws.

LED Greenlight SKU: 45W 4' T8 Strip Retrofit

GL-T8-SRK-4F-45W-3500K-95CRI
GL-T8-SRK-4F-45W-4100K-95CRI
GL-T8-SRK-4F-45W-5000K-95CRI

STRIP Fixture + LED RETROFIT = LAMP

