

2-T8 4' Strip Lamp LED Retrofit Kit

Retrofit Upgrade kit attaches directly
to existing T8 Strip Lamp.
Fresh New Appearance without
demolition of existing fixtures!

36W 4140 Lumens
95 CRI
DLC Listed



FEATURES & BENEFITS

Easy Installation – Attaches over existing fixture
using 4 self-tapping screws

No Ballast

>50% Energy Savings over fluorescent

High Luminance and Low Power consumption

Long Service Life 10X longer life than fluorescent

Wide-Light Distribution

High CRI 95

No UV, No RF interference

No Mercury, RoHS compliant

Instant ON and No Flicker

SPECIFICATIONS

average wattage	36 Watts
luminous efficacy	115 lm/W
input voltage	120-277 VAC
color temps offered (ANSI)	3500K, 4100K or 5000K
CRI (color rendering index)	95 CRI
measured output	4041 lumens
illumination Angle	180 degrees
dimensions (MOL)	4 feet
life span	>100,000 hours
operating temperature	-4°F-122°F (-20°C-50°C)
ratings	dry location
warranty	7 years non-prorated
certification	DLC, ETL
Driver	External Driver - Integrated
power factor	>95% (277 VAC) :

INSTALLATION

- 1) Remove Fluorescent Lamps and Tombstones from Fixture
- 2) Open fixtures electrical access panel and attach "Quik-Connect" jack to input power line to ballast.
- 3) Connect fixtures power "Quik-Connect" to retrofit lamp.
- 4) Install retrofit over fixture-base via 4 self-tapping screws.

LED Greenlight SKU: 36W 4' T8 Strip Retrofit

GL-T8-SRK-4F-36W-3500K-95CRI

GL-T8-SRK-4F-36W-4100K-95CRI

GL-T8-SRK-4F-36W-5000K-95CRI

STRIP Fixture + LED RETROFIT = LAMP

