

LED 4' Strip Lamp

46W 5300 Lumen
95CRI



FEATURES & BENEFITS

Easy Installation
No Ballast
>50% Energy Savings over fluorescent
High Luminance and Low Power consumption
Long Service Life 10X longer life than fluorescent
Wide-Light Distribution-Uniform Distribution
High CRI 95
No UV, No RF interference
No Mercury, RoHS compliant
Instant ON and No Flicker
Housing: Die-Formed Cold-Rolled Steel
Shade: High Transmission Acrylic
Certification: ETL and DLC

SPECIFICATIONS

average wattage	46 Watts
luminous efficacy	115 lm/W
input voltage	120-277 VAC
color temps offered (ANSI)	4000K
CRI (color rendering index)	95 CRI
measured output	5300 lumens
illumination angle	180 degrees
dimensions (MOL)	48" x 4.4" x 3.3" (LxWxH)
life span	>100,000 hours
operating temperature	-4°F-122°F (-20°C-50°C)
ratings	dry location
warranty	7 years non-prorated
certification	DLC, ETL
Driver	External Driver - Integrated
power factor	>95% (277 VAC) :

LED Green Light LED Strip Lamp
Model Number

GL-648STD1-HE-48W-4000K



www.ledgreenlightint.com